

CANAWELD TIG TORCH

(CAN-SG18FX-S1-25-SL-WR1-WF1-GS4)

PROGRIP PKG X 25FT C/W SURELOK ENDS

A new, high-end range of products specified at full performance levels

Features

Consumable parts

- ◆ All wear and spare parts are fully interchangeable with the OEM

Torch Heads

- ◆ All Progrid Ergo Tig torch heads are 100% Weldcraft interchangeable.

Options Include:

- Standard
- Flexible
- Multijust™

Knuckle Joint

- ◆ Small movements of the handle and neck are possible independent of the cable assembly

Cable Systems

- ◆ Progrid cables are constructed from PVC.
- ◆ Power cable, gas and water hoses are colour-coded for ease of identification and protected with a full length neoprene sheath.
- ◆ Progrid R series cables utilize an upgraded Rubber jacket on the power cables

Switches

- ◆ Fitted with a microswitch as standard with an optional blank cover.

Rear End Terminations

- ◆ An extensive range of alternate terminations ensures EU/UK compatibility



TECHNICAL DATA	CAN-SG18FX-S1-25-SL-WR1-WF1-GS4
Cooling Method	Water-Cooled
Rating: DC	380A
Rating: AC	270A
Duty Cycle	100%
Electrode Size	1.0 - 4.0
Water cooling min. flow rate	1.0L/min
Minimum water inlet pressure	2.0Bar
Maximum water inlet pressure	5.0Bar
Maximum water inlet	50°C
Minimum cooling power	900W
Product conforms to EN60974-7, CE, © and are RoHS2, REACH and WEE compliant	