

CANAWELD TIG TORCH

**(CAN-SG26V-N-12-SL-GS5) PROGRIP PKG X 12FT C/W SURELOK ENDS,
NO SWITCH AND SWITCH WIRE, 1.5M GAS HOSE 1/4" BSP FITTINGS**

A new, high-end range of products specified at full performance levels

Features

Consumable parts

- ◆ All wear and spare parts are fully interchangeable with the OEM

Torch Heads

- ◆ All Progrip Ergo Tig torch heads are 100% Weldcraft interchangeable.

Options Include:

Standard

Flexible

Multijust™

Handles

- ◆ Two sizes of handle are utilized for the range.
- ◆ The ergonomically superior Tig handles feature large area soft grips, knuckle joints and screwless "plug and play" switch interchangeability.

Rear End Terminations

- ◆ An extensive range of alternate terminations ensures EU/UK compatibility

Switches

- ◆ Fitted with a microswitch as standard with an optional blank cover.

Cable Systems

- ◆ Progrip cables are constructed from PVC.
- ◆ Power cable, gas and water hoses are colour-coded for ease of identification and protected with a full length neoprene sheath.
- ◆ Progrip R series cables utilize an upgraded Rubber jacket on the power cables



TECHNICAL DATA	CAN-SG26V-N-12-SL-GS5
Cooling Method	Air-Cooled
Rating: DC	180A
Rating: AC	125A
Duty Cycle	35%
Electrode Size	1.0 - 4.0
Water cooling min. flow rate	-
Minimum water inlet pressure	-
Maximum water inlet pressure	-
Maximum water inlet	-
Minimum cooling power	-
Product conforms to EN60974-7, CE, © and are RoHS2, REACH and WEE compliant	