

### MATRIX 3000 AC/DC

Based on the very latest IGBT inverter technology, TIG power source with high frequency arc striking and equipped with an innovative digital panel for the complete control of all the welding parameters. The excellent technical characteristics of this welding machine, coupled with the high technology of its digital control, allow high quality TIG welding, suitable for the toughest industrial applications and maintenance. Highly technologically advanced, robust and user friendly, MATRIX 3000 AC/DC can be used for TIG welding of all metals, including aluminium and its alloys. MATRIX 3000 AC/DC also offers excellent performance in MMA welding with the most difficult basic and cellulosic electrodes.

### Main Features

#### coldTACK

Innovative spot welding device to achieve precise and safe joining with a minimal thermal input. "Multi-cold-TACK" function grants cold spotting in a rapid sequence, thus further widening the benefits of the single spot. Thanks to "Perfect-Point" function, coldTACK allows to obtain the most precise spot positioning.

#### ULTRA FAST PULSE – Pulsazione ad alta frequenza

Pulse TIG welding allows a better arc control and less deformation of the workpiece. The possibility of utilizing very high pulse frequency, up to 2000 Hz, ideal for welding thin thickness, enables to obtain a remarkable reduction in the arc cone and in the thermally altered area, by also having a more stable and concentrated arc together with an increase in both penetration and speed too.

#### VRD – Voltage Reduction Device

VRD device reduces the open circuit voltage to values below 12 V, by enabling the use of the machine in highly hazardous environments for the operator's maximum safety.

### Features

- ◆ Compact and innovative design
- ◆ Metallic main structure with shock-proof fibre compound front panel
- ◆ Control panel protected against accidental impact
- ◆ Robust handle integrated into the chassis
- ◆ Reduced weight and size, easy-to-carry



#### EASY PULSE

Pulse TIG welding allows a better arc control and a contained workpiece deformation. The ability of choosing a high value of pulse frequency (up to 500 Hz) allows to achieve a more concentrated arc cone, ideal for welding thin materials. "EASY PULSE" feature, in function of the chosen peak current, will synergically generate, in a simple and automatic way, both an adequate pulse frequency (between 0.5 and 500 Hz) and a base current. Pulse parameter values preselected in the control will save setting time, by ensuring the best possible pulse parameter combinations, ideal for less skilled welders/operators.

#### CYCLE

"CYCLE" function allows, by simply pressing the torch trigger, continuously switching between two current values, previously preselected. This function is most suitable for welding different thickness profiles, requiring a continuous current adjustment change. In welding aluminium, the ability of using a higher start current favours the workpiece preheating.

- ◆ High performance on thin metal sheets Automatic compensation for mains voltage fluctuations within +20% -20%
- ◆ Use of special TIG torches will enable the remote control of the welding parameters directly from the torch

Headquarters:

No. P6-072

Sharjah Airport Int'l Free Zone (SAIF)

P.O. Box : 120927

Sharjah - U.A.E

Tel : +9716 5575516 / 5575517 / 5578852

Fax : +971 6 5575518

Mobile : +97150 6524818

Email : info@gte.ae

Website : www.gte.ae

- ◆ Excellent TIG welding characteristics
- ◆ High frequency arc striking, precise and efficient even from long distance
- ◆ Very good MMA welding characteristics with any type of electrodes

- ◆ Low energy consumption
- ◆ Easy-to-use
- ◆ Standard equipped with pulse mode integrated into the control with available "easy-pulse" facility
- ◆ Digital control of all the welding parameters

### Accessories (Included)

- ◆ Welding cable including earth clip
- ◆ TIG torch

### Optional Accessories

- ◆ Electrode holder and welding cable
- ◆ Argon regulator
- ◆ Auto-Darkening Welding Helmet

TECHNICAL DATA		MATRIX 3000 AC/DC
Three Phase Input 50/60 Hz	V +20% -20%	400
Input Power @ I <sub>2</sub> Max	kVA	9,6
Delayed Fuse (I <sub>2</sub> @ 100%)	A	10
Power Factor / cos φ		0,95/0,99
Efficiency Degree		0,76
Open Circuit Voltage	V	100
Current Range	A	5-300
Duty Cycle at (40°C)	A 100%	210
	A 60%	250
	A 30%	300
Standards		EN 60974-1 ■ EN 60974-3 ■ EN 60974-10
		<b>S</b>
Protection Class	IP	23 S
Insulation Class		F
Weight ( kg )		19
Dimensions (mm) W x L x H		495 x 185 x 390